

JOHN DEERE

alimentazione gasolio
1500 giri/ - 1500 r.p.m.
Telaio aperto - Skid



Modello	Potenza 50HZ PRP		Potenza 50HZ LTP		Potenza 60HZ PRP		Potenza 60HZ LTP		MOTORE				Consumi 75% Lt./h		Dimensioni (LxWxH) mm	Peso Kg.	Serb. Lt.	
	KVA	KW	KVA	KW	KVA	KW	KVA	KW	Tipo	Cil.	Asp.	Lt.	Reg.	50Hz				60Hz
30.JD.SK	30	24	34	27	35	28	38	30	3029DF128	3	N	2,9	M	4,6	6,1	1500x780x1300	690	73
40.JD.SK	40	32	44	35	45	36	50	40	4039DF008	4	N	3,9	M	6,6	7,8	1650x750x1300	850	78
60.JD.SK	60	48	66	53	71	57	78	62	4039TF008	4	T	3,9	M	9,5	11,2	1650x750x1300	1090	78
80.JD.SK	80	64	88	70	90	72	100	80	4045TF258	4	T	4,5	M	12,1	13,7	1800x800x1480	1150	82
100.JD.SK	100	80	110	88	125	100	138	110	4045HF258	4	TA	4,5	M	14,7	18,8	2000x800x1540	1250	90
120.JD.SK	120	96	132	106	142	114	156	125	6068TF258	6	T	6,8	M	16,4	21,6	2200x800x1540	1410	95
150.JD.SK	150	120	165	132	190	152	209	167	6068HF158	6	TA	6,8	M	22,3	28,4	2300x800x1540	1620	100
180.JD.SK	180	144	200	160	208	166	229	183	6068HF258	6	TA	6,8	M	27,3	31,6	2450x800x1540	1780	104
200.JD.SK	200	160	220	176	230	184	253	202	6081HF001	6	TA	8,1	M	29,2	34	2600x1150x1880	2020	120
250.JD.SK	250	200	275	220	280	224	308	246	6081HF001	6	TA	8,1	M	36,4	43,2	2600x1150x1880	2100	120
270.JD.SK	270	216	300	240	288	230	335	268	6081HF001	6	TA	8,1	M	37,8	44,5	2700x1150x1880	2200	130

JOHN DEERE

alimentazione gasolio
1500 giri/ - 1500 r.p.m.
Cofano insonorizzante - Soundproof canopy

Modello	Potenza 50HZ PRP		Potenza 50HZ LTP		Potenza 60HZ PRP		Potenza 60HZ LTP		MOTORE				Consumi 75% Lt./h		Dimensioni (LxWxH) mm	Peso Lt./h	Serb. Lt./h	
	KVA	KW	KVA	KW	KVA	KW	KVA	KW	Tipo	Cil.	Asp.	Lt.	Reg.	50Hz				60Hz
30.JD.SP	30	24	34	27	35	28	38	30	3029DF128	3	N	2,9	M	4,6	6,1	2150x955x1480	1010	50
40.JD.SP	40	32	44	35	45	36	50	40	4039DF008	4	N	3,9	M	6,6	7,8	2470x955x1480	1245	50
60.JD.SP	60	48	66	53	71	57	78	62	4039TF008	4	T	3,9	M	9,5	11,2	3100x1150x1580	1500	50
80.JD.SP	80	64	88	70	90	72	100	80	4045TF258	4	T	4,5	M	12,1	13,7	3100x1150x1580	1585	120
100.JD.SP	100	80	110	88	125	100	138	110	4045HF258	4	TA	4,5	M	14,7	18,8	3100x1150x1580	1660	120
120.JD.SP	120	96	132	106	142	114	156	125	6068TF258	6	T	6,8	M	16,4	21,6	3100x1150x1580	1820	120
150.JD.SP	150	120	165	132	190	152	209	167	6068HF158	6	TA	6,8	M	22,3	28,4	3500x1220x1880	2250	120
180.JD.SP	180	144	200	160	208	166	229	183	6068HF258	6	TA	6,8	M	27,3	31,6	3500x1220x1880	2450	120
200.JD.SP	200	160	220	176	230	184	253	202	6081HF001	6	TA	8,1	M	29,2	34	4000x1220x1880	2820	120
250.JD.SP	250	200	275	220	280	224	308	246	6081HF001	6	TA	8,1	M	36,4	43,2	4000x1220x1880	2950	120
270.JD.SP	270	216	300	240	288	230	335	268	6081HF001	6	TA	8,1	M	37,8	44,5	4000x1220x1880	3050	120